



ENSURING SUSTAINABLE
POWER



GENERATING SETS



WATER COOLED



THREE PHASES



60 HZ



DIESEL

Service		Standby	Prime
Power	kVA	1500	1363
Power	kW	1200	1090
Rated Speed	r.p.m	1800	
Standart Voltage	V	400/230	
Rated At Power Factor		0.8	

IPS Company with quality certification ISO 9001

IPS gensets are compliant with EC mark which includes the following directives:

- 2006/42/EC Machinery safety.
- 2014/30/EU Electromagnetic compatibility.
- 2014/35/EU Electrical equipment designed for use within certain voltage limits
- 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- 97/68/EC Emissions of gaseous and particulate pollutants. (amended by 2002/88/EC & 2004/26/EC)
- EN 12100, EN 13857, EN 60204

SPECIFICATIONS

ENGINE

Engine		Specifications
Engine Power Output	<i>kWm/hp</i>	1320/1769
Manufacturer		MITSUBISHI
Model		S12R-PTA
Engine Speed	<i>r.p.m</i>	1800
Injection Type		DIRECT
Number of cylinder		12V
Bore and Stroke	<i>mm</i>	170x180
Displacement	<i>L</i>	49.03
Cooling System		WATER COOLED
Fuel Consumption 50% PRP	<i>l/h</i>	170
Fuel Consumption 75% PRP	<i>l/h</i>	213
Fuel Consumption 100 % PRP	<i>l/h</i>	282
Total oil capacity including tubes, filters	<i>L</i>	180
Total coolant capacity	<i>L</i>	335
Governor	<i>Type</i>	Electronic
Electric system voltage(V)	<i>V</i>	24 Vdc

ALTERNATOR

Alternator		Specifications
Design		Brushless single bearing
Stator		2/3 pitch
Output Voltage	<i>V</i>	400/230
Frequency	<i>HZ</i>	60
Automatic Voltage Regulation	<i>±%</i>	1
Standard Temp. Rise	<i>C</i>	125 - 163°C Continuous
Number of Wires		4
Phase Rotation		A (U), B (V), C (W)
Protection Class		Class H
Standard degree of protection		IP23
Rotor		Single bearing, flexible disc

Prime Power (PRP):


According to ISO 8528-1:2005, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24 h of operation shall not exceed 70 % of the PRP.

Emergency Standby Power (ESP):

According to ISO 8528-1:2005, Emergency standby power is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP.

Note: All data based on operation to ISO 3046/1, BS 5514 and DIN 6271 standard reference conditions

DIMENSIONS




OPEN SET

LxWxH	mm	LxWxH	4390x2040x2218
Weight	kg	Weight	9330
Fuel Tank	lt	Fuel Tank	2000

OPEN TYPE FEATUERS:

The complete gen-set is mounted as whole on a heavy-duty fabricated, steel base frame

- Anti-vibration pads are fixed between the engine/ alternator feet and the base frame
- Base frame design incorporates an integral fuel tank (Up to 750 kVA)
- The generating set can be lifted or carefully pushed / pulled by the base frame
- Dial type fuel gauge and drain plug on the fuel tank
- Forklift pockets within base frame (up to 500kVA)



CANOPIED

LxWxH	mm	LxWxH	6058x2438x2591
Weight	kg	Weight	14630
Fuel Tank	lt	Fuel Tank	2000

Sound Proof Canopy

- Special design for minimizing acoustic level.
- Galvanized steel construction further protected by polyester powder coat paint.
- Black finish stainless steel locks and hinges.
- Control panel viewing window in a lockable access door.
- Emergency stop push button (red) mounted on enclosure exterior.
- Lifting, drag and jacking points on base frame.
- Radiator fill via removable, flush mounted rain cap fitted with compression seal.
- Acoustic insulation with moisture-repellent and non-flammable material
- Exhaust Silencer is Protected against environmental influences.
- All canopy are designed with modular principles without welding assembly.

Control System

Control supervision and protection panel is mounted on the genset base frame. The control panel is equipped as follows:

1. Auto Mains Failure Control Panel

Panel equipments:

- Control with AMF module
- Static battery charger
- Emergency stop push button



DSE 7320

a. Generating set control module DSE 7320 features

- The module is used to monitor a mains supply and starts and stops a standby generating set.
- Micro-processor based design.
- Automatic control of mains and generator contactors.
- Monitors engine performance and AC power output.
- LED alarm indication.
- Front panel configuration of timers and alarm trip points.
- Easy push button control STOP/RESET
- MANUAL - TEST - AUTO - MUTE ALARM - START.

b. Metering via LED display

- Generator Volts (L-L / L-N)
- Engine oil pressure (PSI-Bar)
- Generator Ampere (L1,L2,L3)
- Engine temperature (°C&°F)
- Generator Frequency (Hz)
- Plant battery volts
- Engine hours run
- Mains Volts (Ph-Ph/Ph-N)
- Generator kVA, kWh
- Generator kW as % of rated kW setting
- Generator Cos (σ)

c. Alarms

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- Charge fail
- Over Current
- Under / Over Generator Voltage
- Low Oil Pressure
- Emergency stop
- High engine temperature
- kW overload
- Unbalanced load
- Independent earth fault trip

d. LED indications

Four configurable LED's like:

- Mains available
- Generator available
- Mains on load
- Generator on load

2. Power Outlet Terminal Board Mounted on the Genset Base Frame.



ENSURING SUSTAINABLE
POWER